


WEDOLiT FN 8830

Special forming oil

WEDOLiT FN 8830 is a chlorine free, pasty, water-insoluble lubricant for cold forming processes (e.g. pilgering) of high alloyed steels. The product is usually applied on the outer diameter by brushes or by means of rollers.



Physical Properties Typical Data

:		
:	0.00	
:	0.0	
:	0	
:		

Application Guidelines

Storage must be frost-free between 41 - 104°F (5 - 40°C).
The minimum durability is 24 months in an original sealed package.

Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:
https://2trim.us/diw/?plr=FN-8830*en-ap*ap

WEDOLiT FN 8830
©2020-2024 Master Fluid Solutions™ | 2024-04-26



Choose WEDOLiT FN 8830:

- Stable load carrying capacity and a homogenous sliding behavior
- Reduces friction and wear and thus contributes to a high tool life
- The outstanding extreme-pressure properties combined with an exceptional adhesion offers the possibility for high degrees of deformation
- Stable cold start behavior, prevents stick-slip and chatter
- Contributes to achieving dimensional accuracy
- Pigments will remain on the surface after annealing and need to be removed (e.g. by pickling with HCl or HNO₃) before further processing

Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.