

TRIM™ TC 177

Odor Mask

TRIM TC 177 is a "vanilla" odor mask. This product may be used to reduce some of the odors associated with coolant systems.

Additives



The troubleshooters:

As cutting and grinding fluids can start to break down over time, tank-side additives can solve a number of problems. There are TRIM tank-side additives compatible with most coolants to extend tap and tool life, improve mechanical lubricity, control built-up edge, prevent stained parts, control foam, stabilize the emulsion, and replenish dye.

Whatever your problems and concerns, ask your TRIM specialist if a tank-side additive could be the answer.

Aerospace Approvals

Company	Specification
Raytheon Technologies/Collins Aerospace/Pratt & Whitney	PMC 9133



Choose TC 177:

- "Vanilla" odor mask

TC 177 especially for:

Applications — odor mask

Health and Safety

Request SDS



TRIM™ TC 177

Odor Mask



Application Guidelines

- Very small amounts may be added directly to the working solution to reduce odor.
- Typical application rates are less than 6 ounces per 10,000 gallons.
- For additional product application information, including performance optimization, please contact your Master Fluid Solutions' Authorized Distributor at <https://www.masterfluids.com/ap/en-ap/distributors/index.php>, your District Sales Manager, or email us at apac-info@masterfluids.com.

Physical Properties Typical Data

Color (Concentrate)	Colorless
Odor (Concentrate)	Vanilla
Form (Concentrate)	Liquid
Flash Point (Concentrate) (ASTM D92-90)	> 100°C
pH (Concentrate as Range)	3.5 - 3.9

Ordering Information

20-liter pail

204-liter drum

TRIM™ TC 177 | ©1977-2025 Master Fluid Solutions™ | 2025-12-16

Additional Information

- Use Master STAGES™ Whamex™ for a quick and thorough precleaning of your machine tool and coolant system.
- Consult Master Fluid Solutions before using on any metals or applications not specifically recommended.
- This product should not be mixed with other metalworking fluids or metalworking fluid additives, except as recommended by Master Fluid Solutions, as this may reduce overall performance, result in adverse health effects, or damage the machine tool and parts. If contamination occurs, please contact Master Fluid Solutions for recommended action.
- TRIM™ is a trademark of Master Chemical Corporation d/b/a Master Fluid Solutions.
- Master STAGES™ and Whamex™ are trademarks of Master Chemical Corporation d/b/a Master Fluid Solutions.
- The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:

https://2trim.us/di/?i=ap_en-ap_TC177



4/F, Block H, No. 200 Jinsu Road Pudong,
Shanghai

上海市浦东新区金苏路200号H栋4楼,
201206

China

+86 21 6807-0101, 400-801-3590

info@masterchemical.com.cn

[masterfluids.com/ap/en-ap/](https://www.masterfluids.com/ap/en-ap/)

