

WEDOLiT® AS 4111

Special-Fluid 60°C flash point

WEDOLiT AS 4111 is a leading edge universally applicable, corrosion protection which offers a long-term protection for indoor storage. It has been especially developed for loosening rusted parts and can be applied by spraying, flooding or via an immersion bath.



Physical Properties Typical Data

| Parameter | Typical results | Tested according to |
|-------------------------|------------------------|-----------------------|
| Appearance: | Medium-brown, clear | Visual |
| Density at 15°C: | 0.83 g/cm ³ | ASTM D 7042 |
| Viscosity at 20°C: | 4.4 mm ² /s | ASTM D 7042 |
| Flash point: | > 60 °C | DIN EN ISO 2719 |
| Film weight: | 1.8 g/m ² | Dipping procedure |
| Film type: | Oily | Haptical |
| Dewatering effect: | ≤ 60 s | Internal test method |
| Water separation: | 5 min | Internal test method |
| Humidity test: | 70 cycles | DIN EN ISO 6270-2 AHT |
| Salt spray performance: | 8 h | DIN EN ISO 9227 NSS |

Application Guidelines

Storage must be frost-free between 5 - 35°C.

The minimum durability is 12 months in an original sealed package.

Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:
https://2trim.us/diw/?plr=AS-4111*en*eu

WEDOLiT® AS 4111

©2017-2026 Master Fluid Solutions™ | 2026-06-27



Choose WEDOLiT AS 4111:

- Suitable for overseas transport
- Rust remover for humidity-related ignition problems in electrical systems
- Loosens rusted screws, nuts, joints, hinges, switches and mechanisms
- Cleans dirty tools and components and protects them from corrosion
- Stable against acidic and alkaline impurities
- Easily removable with organic solvents (cold cleaners) or water-miscible alkaline industrial cleaners
- Water displacing with very good wetting behaviour
- Additive loss due to water contact: Low

Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

Hasselsstraße 6-14
Düsseldorf, 40597
Germany
+49 211 41 72 82 00

info-eu@masterfluids.com

[masterfluids.com/eu/en/](https://www.masterfluids.com/eu/en/)

