


WEDOLiT CN 5370-22

High-performance cutting oil

WEDOLiT CN 5370-22 is a low viscous, non-water soluble, high performance cutting oil for thread cutting operations, which is based on the latest base-oil-technology. The product is also suitable for general cutting operations of high alloyed steels, cast iron, aluminium and non-ferrous metals.



Physical Properties Typical Data

| Parameter | Typical results | Tested according to |
|--------------------|-------------------------|---------------------|
| Appearance: | Brown, clear | Visual |
| Density at 20°C: | 0.87 g/cm ³ | ASTM D 7042 |
| Viscosity at 40°C: | 22.0 mm ² /s | ASTM D 7042 |
| Flash point: | > 170 °C | DIN EN ISO 2719 |
| Copper corrosion: | Not determined* | DIN 51759-1 |

*Discolourations of non-ferrous metals should be examined in preliminary tests

Application Guidelines

Storage must be frost-free between 5 - 40 °C.
The minimum durability is 24 months in an original sealed package.

Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:
https://2trim.us/diw/?plr=CN-5370-22*en*eu

WEDOLiT CN 5370-22
©2016-2024 Master Fluid Solutions™ | 2024-04-26



Choose WEDOLiT CN 5370-22:

- High performance product, which leads to an excellent surface finish and dimensional accuracy
- Special additivition for thread cutting operations
- Highly reduced oil mist formation, almost no loss of evaporation
- Reduces friction and wear and thus contributes to a long tool life
- Offers high cooling properties with a very good wetting behaviour
- Very good flushing behaviour with an optimal transport of chips and swarf
- Easily removable with organic solvents or alkaline industrial cleaners

Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

Hasselsstraße 6-14
Düsseldorf, 40597
Germany
+49 211 41 72 82 00

info-eu@masterfluids.com
masterfluids.com/eu/en/

