# WEDOLIT® EP 540 CM

## Expander oil

**WEDOLIT EP 540-CM** is a highly viscous, high-performance, mineral-oil-based forming oil. The product has been developed to the highest technical standard for the utilization in the pipe industry (e.g. manufacturing of large diameter pipes, for gas and oil pipelines). The product can be used undiluted and prevents, due to the high content of polar additives, the stick-slip-effect.







### **Physical Properties Typical Data**

Parameter	Typical results	Tested according to	
Appearance:	Brown, viscous	Visual	
Density at 20°C:	0.95 g/cm <sup>3</sup>	ASTM D 7042	
Viscosity at 40°C:	> 360.0 mm <sup>2</sup> /s	ASTM D 7042	
VKA-value:	> 4000 N (typ. 4200 N)	DIN 51350 T2	
Copper corrosion:	1	DIN EN ISO 2160	

Mineral oil	Ester	EP-additives	AW-additives	Zn-additives	Chlorine
+	+	+	+	-	•

# **Application Guidelines**

The product should be stored frost-free, between 10 - 40°C. The minimum durability is 12 months in an original sealed package.

### Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL: https://2trim.us/diw/?plr=EP-540-CM\*en\*eu

WEDOLIT<sup>®</sup> EP 540 CM ©2022-2025 Master Fluid Solutions ™ | 2025-12-05



#### **Choose WEDOLIT EP 540 CM:**

- Very high film stability (even under high pressures)
- Good adhesion properties on smooth surfaces, very good wear protection
- Easily removable with water (spontaneous emulsification)
- The emulsion can be used for preand post-cleaning of the pipes and the expander head and can be separated into water and oily waste by the utilization of specific additives
- The treated water can be reused for the preparation of a new emulsion (to a certain degree)

### **Health and Safety**

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

Hasselsstraße 6-14 Düsseldorf, 40597 Germany +49 211 41 72 82 00

info-eu@masterfluids.com

masterfluids.com/eu/en/

