WEDOLIT EP 760-CM

Expander oil

WEDOLIT EP 760-CM is a highly viscous, high-performance, mineral-oil-based forming oil. The product has been developed to the highest technical standard for the utilization in the pipe industry (e.g. manufacturing of large diameter pipes, for gas and oil pipelines). The product can be used undiluted and prevents, due to the high content of polar additives, the stickslip-effect.



Physical Properties Typical Data

Parameter		Typical results			Tested according to		
Appearance:		Brown, viscous			Visual		
Density at 20°C:		0.95 g/cm ³			ASTM D 7042		
Viscosity at 40°C:		> 320.0 mm²/s			ASTM D 7042		
VKA-value:		> 6000 N (typ. 6000 N)			DIN 51350 T2		
Copper corrosion:		1			DIN EN ISO 2160		
Mineral oil	Ester	EP-additives	AW-additives	Zr	Zn-additives Chlorine		
+	+	+	+		-	-	

Application Guidelines

The product should be stored frost-free, between 10 - 40°C. The minimum durability is 12 months in an original sealed package.

Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL: https://2trim.us/diw/?plr=EP-760-CM*en*eu

WEDOLiT EP 760-CM ©2022-2024 Master Fluid Solutions™ | 2024-04-27





Choose WEDOLIT EP 760-CM:

- Very high film stability (even under high pressures)
- Good adhesion properties on smooth surfaces, very good wear protection
- Easily removable with water (spontaneous emulsification)
- The emulsion can be used for preand post-cleaning of the pipes and the expander head and can be separated into water and oily waste by the utilization of specific additives
- The treated water can be reused for the preparation of a new emulsion (to a certain degree)

Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

> Hasselsstraße 6-14 Düsseldorf, 40597 Germany +49 211 41 72 82 00

info-eu@masterfluids.com

masterfluids.com/eu/en/