

# WEDOLiT® FN 4170-35

## Chlorinated stamping oil

WEDOLiT FN 4170-35 is a low viscous, water-insoluble chlorinated lubricant for heavy forming operations of steel and stainless steel. A combination of EP additives offers an outstanding performance for precision cutting operations. The undiluted product is usually applied by spraying, dipping, brushes or by means of rollers.



### Physical Properties Typical Data

Parameter	Typical results	Tested according to
Appearance:	Light brown, clear	Visual
Density at 20°C:	1.00 g/cm <sup>3</sup>	ASTM D 7042
Viscosity at 40°C:	36.0 mm <sup>2</sup> /s	ASTM D 7042
Flash point:	> 150 °C	DIN EN ISO 2719
Copper corrosion:	1a	DIN 51759-1

### Application Guidelines

Storage must be frost-free between 5 - 40°C.


The minimum durability is 24 months in an original sealed package.

### Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:  
[https://2trim.us/diw/?plr=FN-4170-35\\*en\\*eu](https://2trim.us/diw/?plr=FN-4170-35*en*eu)

WEDOLiT® FN 4170-35

©2020-2025 Master Fluid Solutions™ | 2025-12-19



### Choose WEDOLiT FN 4170-35:

- Stable load carrying capacity and a homogenous sliding behaviour
- Reduces friction and wear and thus contributes to a high tool life
- Outstanding wetting ability and film formation without adhesion
- Stable cold start behaviour, prevents stick-slip and chatter
- Leads to clean surfaces and contributes to achieving dimensional accuracy
- Easily removable with organic solvents or alkaline industrial cleaners

### Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

Hasselsstraße 6-14  
Düsseldorf, 40597  
Germany  
+49 211 41 72 82 00

[info-eu@masterfluids.com](mailto:info-eu@masterfluids.com)

[masterfluids.com/eu/en/](https://masterfluids.com/eu/en/)