

WEDOLiT® FS 4101

Evaporating forming oil

WEDOLiT FS 4101 is a low-viscosity, solvent-based lubricant suitable for stamping and bending operations on steel, aluminium and non-ferrous metals. The product is usually applied undiluted by spraying, flooding, brushing or by means of felt rollers.



Physical Properties Typical Data

Parameter	Typical results	Tested according to
Appearance:	Transparent	Visual
Density at 20°C:	0.79 g/cm ³	ASTM D 7042
Viscosity at 20°C:	1.9 mm ² /s	ASTM D 7042
Flash point:	> 65 °C	DIN EN ISO 2719
Copper corrosion:	Not determined*	DIN 51759-1

*Discolourations of non-ferrous metals should be examined in preliminary tests

Application Guidelines

The product must be stored frost-free between 5-40 °C.

The minimum shelf life in the sealed original container is 24 months.

Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL: https://2trim.us/diw/?plr=FS-4101*en*eu

WEDOLiT® FS 4101

©2026 Master Fluid Solutions™ | 2026-06-15



Choose WEDOLiT FS 4101:

- Very good spreading effect, resulting in an optimal and uniform wetting of the metal surface
- Stable load-bearing capacity and homogeneous sliding properties
- Reliably reduces friction and wear and thus contributes to long tool life
- Leads to clean surfaces and contributes to the achievement of dimensional accuracy
- If finely applied, the product evaporates after a short time almost without leaving any residue, so that additional cleaning of the workpieces is not necessary. Otherwise, the product can be easily removed with solvent-based or alkaline cleaners

Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

Hasselsstraße 6-14
Düsseldorf, 40597
Germany
+49 211 41 72 82 00

info-eu@masterfluids.com

[masterfluids.com/eu/en/](https://www.masterfluids.com/eu/en/)

