

WEDOLiT® FS 6311

Evaporating forming oil

WEDOLiT FS 6311 is a low viscous, solvent-based lubricant for stamping and forming operations of steel, aluminium and non-ferrous metals, which also performs excellently in thread rolling operations (aluminium). The undiluted product is usually applied by spraying, flooding, brushes or by means of rollers.



Physical Properties Typical Data

| Parameter | Typical results | Tested according to |
|--------------------|------------------------|---------------------|
| Appearance: | Transparent | Visual |
| Density at 20°C: | 0.79 g/cm ³ | ASTM D 7042 |
| Viscosity at 20°C: | 3.9 mm ² /s | ASTM D 7042 |
| Flash point: | > 80 °C | DIN EN ISO 2719 |
| Copper corrosion: | Not determined* | DIN 51759-1 |

*Discolourations of non-ferrous metals should be examined in preliminary tests

Application Guidelines

Storage must be frost-free between 5 - 40°C.

The minimum durability is 24 months in an original sealed package.

Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL: https://2trim.us/diw/?plr=FS-6311*en*eu

WEDOLiT® FS 6311

©2020-2026 Master Fluid Solutions™ | 2026-03-06



Choose WEDOLiT FS 6311:

- Good spreading behaviour, which leads to a uniform wetting of the metal surface
- Stable load carrying capacity and a homogenous sliding behaviour
- Reduces friction and wear and thus contributes to a high tool life
- Leads to clean surfaces and contributes to achieving dimensional accuracy
- If the product is finely dispersed, it evaporates after a short time without leaving any residues. Therefore, an additional cleaning step is not necessary. Otherwise, it is easily removable with organic solvents or alkaline industrial cleaners

Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

Hasselsstraße 6-14
Düsseldorf, 40597
Germany
+49 211 41 72 82 00

info-eu@masterfluids.com

[masterfluids.com/eu/en/](https://www.masterfluids.com/eu/en/)