

WEDOLiT® FS 7400

Calibration Oil

WEDOLiT FS 7400 is a non-water-miscible, evaporating calibration oil for light to medium calibration processes.



Physical Properties Typical Data

| Parameter | Typical results | Tested according to |
|--------------------|------------------------|---------------------|
| Appearance: | yellowish, clear | Visual |
| Density at 20°C: | 0.79 g/cm ³ | ASTM D 7042 |
| Viscosity at 20°C: | 3.5 mm ² /s | ASTM D 7042 |
| Flash point: | > 61 °C | DIN EN ISO 2719 |
| Copper corrosion: | Not determined* | DIN 51759-1 |

*Discolourations of non-ferrous metals should be examined in preliminary tests

Application Guidelines

Please test material compatibility on the materials used.
The product must be stored frost-free between 5 - 40°C.
The minimum shelf life in the sealed original container is 12 months.

Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:
https://2trim.us/diw/?plr=FS-7400*en*eu

WEDOLiT® FS 7400
©2022-2026 Master Fluid Solutions™ | 2026-04-30



Choose WEDOLiT FS 7400:

- Can be applied by dipping or spraying
- The residues left on the surfaces after calibration evaporate completely during annealing

Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

Hasselsstraße 6-14
Düsseldorf, 40597
Germany
+49 211 41 72 82 00

info-eu@masterfluids.com

[masterfluids.com/eu/en/](https://www.masterfluids.com/eu/en/)

