


WEDOLiT® FW 9200 (C 66)

Water soluble, especially for drawing brass cases

WEDOLiT FW 9200 is an ester-based, water-miscible forming lubricant, which can be universally applied in forming (especially drawing) processes of brass and non-ferrous metals.

The application concentration depends on the level of difficulty of the forming operations and has to be determined in preliminary tests. Concentrations of 10 - 15% are usually recommended.



Physical Properties Typical Data

Concentrate

Colour	Mineral oil content	Viscosity at 20°C: ASTM D 7042	Density at 20°C: ASTM D 7042	Copper corrosion: DIN 51759-1
Brown	Free	1000.0 mm ² /s	0.98	No attack

5% Solution

Colour	pH-value (tap water)	Corrosion protection DIN 51360-2	Refractometer factor (brix)	Conductivity (Deionised water)
Yellowish	9.5	5 % grade 0	1.0	Not determined

Mineral oil	EP-additives	Chlorine	Boron	Amines	FAD
-	+	-	-	+	-

Application Guidelines

The preparation of the emulsion is carried out by slowly adding the concentrate into water (drinking water quality) under thorough stirring. A more homogenous product is achieved by the use of automatic mixing systems.

Storage must be frost-free between 5 - 40°C.

The minimum durability is 12 months in an original sealed package.

Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL: https://2trim.us/diw/?plr=FW-9200*en*eu

WEDOLiT® FW 9200 (C 66)

©1951-2025 Master Fluid Solutions™ | 2025-12-05



Choose WEDOLiT FW 9200:

- Can be applied undiluted as a concentrate
- Stable load carrying capacity and a homogenous sliding behaviour
- Reduces friction and wear and thus contributes to a high tool life
- Outstanding wetting ability and film formation without adhesion
- Leads to clean surfaces and contributes to achieving dimensional accuracy
- Very good material compatibility
- Easily removable with organic solvents or alkaline industrial cleaners

Recommended mixing ratio

- Drawing operations: 10 - 15%

Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

Hasselsstraße 6-14

Düsseldorf, 40597

Germany

+49 211 41 72 82 00

info-eu@masterfluids.com

masterfluids.com/eu/en/

