WEDOLiT® SA 2

Neutralizer

WEDOLiT SA 2 is used to neutralize the pH value of an emulsion that was treated with a splitting agent. The optimal pH value has to be determined in preliminary tests.



Physical Properties Typical Data

Parameter	Typical results	Tested according to
Appearance:	Yellow-brown, clear	Visual
Density at 20°C:	1.48 g/cm^3	ASTM D 7042
Viscosity at 40°C:	0.0 mm^2/s	ASTM D 7042
pH-value [20%; 70°C]:	14.0	DIN EN ISO 10523

Application Guidelines

Storage must be frost-free between 5 - 40°C.
The minimum durability is 12 months in an original sealed package.

Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL: https://2trim.us/diw/?plr=SA-2*en*eu

©2026 Master Fluid Solutions™ | 2026-11-04

Choose WEDOLiT SA-2:

- Applicable at ambient temperature
- The suitability and the required volume, which depends on the concentration of the expander oil, have to be determined in preliminary tests (laboratory scale)
- To ensure a thorough mixing the product should be added at points with high circulation

Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

Hasselsstraße 6-14
Düsseldorf, 40597
Germany
+49 211 41 72 82 00

info-eu@masterfluids.com

masterfluids.com/eu/en/