


TRIM™ E950

High Performance Machining Emulsion

TRIM E950 is a proprietary blend of new vegetable-based technology and premium traditional lubricity additives to yield a very high performance, low management metal removal fluid. This premium emulsion product is operator friendly because of its mild contact nature and low chemical initial-charge odour. TRIM E950 is robust enough to deliver extended useful life and avoid rancid odours normally associated with traditional emulsions. The unparalleled lubricity delivers exceptional surface finish and tool life on difficult to machine aluminium alloys, inconel, titanium, stainless and high tensile strength steels.

Precision Parts Manufacturer Saves 40% on Cutting Fluid with TRIM™ E950



The customer is a large-scale precision parts manufacturer that serves the aerospace and energy sectors. Their high-volume facility includes more than 40 CNC machines that carry out turning, drilling, machining and grinding operations on challenging materials including aluminium, Inconel®, titanium and stainless steel.

Aerospace Approvals

Company	Specification
GE AVIO	TN0989
Rolls-Royce	CSS 129, CSS 131
Safran Group	PR6300



Choose E950:

- Delivers unparalleled lubricity
- Very long sump life and low carry-off rates result in low operating cost
- Low foam even in soft water areas
- Hard water tolerant
- Non-chlorinated and non-sulphurised extreme pressure (EP) additives control built-up edge (BUE) in tough operations on aerospace materials
- Fine emulsion ensures fast wetting to get the fluid to the point of cut and fully coat the work piece and chips for superior tool life and corrosion prevention
- Compatible with all materials excluding magnesium
- Easily recycled or disposed of without special handling or equipment
- Will run effectively for long periods without the need for costly additives

E950 especially for:

Applications — boring, broaching, deep hole drilling, down the hole work, drilling, gear cutting, heavy-duty machining center work, high-pressure, high-volume, high-speed milling, high-speed turning, honing, milling, reaming, roll threading, tapping, thread forming, thread rolling and turning

Metals — cast aluminium, cast iron, copper, nickel alloys, nonferrous metals, stainless steels, steel alloys, steels, titanium, wrought aluminium and yellow metals

Industries — aerospace, automotive, energy and medical

E950 is free of — boron, chlorine, formaldehyde releasers, nitrites, phenolic compounds and sulphurised EP additives

TRIM™ E950

High Performance Machining Emulsion



Application Guidelines

- Use higher concentrations for lower speed metal cutting operations where maximum lubricity is required and lower concentrations for operations requiring more cooling.
- Running at concentrations between 7 – 10% offers the best sump life and corrosion inhibition.
- For additional product application information, including performance optimisation, please contact your Master Fluid Solutions' Authorised Distributor at <https://www.masterfluids.com/eu/en/distributors/index.php>, your District Sales Manager, or call our Tech Line at +49 211 41 72 8 -900.


Physical Properties Typical Data

Colour (Concentrate)	Light brown
Odour (Concentrate)	Mild amine
Form (Concentrate)	Liquid
Flash Point (Concentrate) (ASTM D93-08)	> 160°C
pH (Concentrate as Range)	8.9 - 9.9
pH (Typical Operating as Range)	8.8 - 9.4
Coolant Refractometer Factor	1.0

Recommended Metalworking Concentrations

Light Duty	5.0% - 8.0%
Moderate Duty	8.0% - 10.0%
Heavy Duty	10.0% - 15.0%
Design Concentration Range	5.0% - 15.0%

Concentration by % Brix



% Concentration = Refractive Reading x Refractive Factor
Coolant Refractometer Factor % Brix = 1.0

Health and Safety

Request SDS



TRIM™ E950

High Performance Machining Emulsion



Mixing Instructions

- Recommended usage concentration in water: 5.0% - 15.0%.
- To help ensure the best possible working solution, add the required amount of concentrate to the required amount of water (never the reverse) and stir until uniformly mixed.
- Use premixed coolant as makeup to improve coolant performance and reduce coolant purchases. The makeup you select should balance the water evaporation rate with the coolant carryout rate. Use our Coolant Makeup Calculator to find the best ratio for your machine: apps.masterfluids.com/makeup/.
- Use mineral-free water to improve sump life and corrosion inhibition while reducing carryoff and concentrate usage.

Ordering Information

20-litre pail

204-litre drum

1000-litre IBC

TRIM™ E950 | ©2010-2025 Master Fluid Solutions™ | 2025-12-19

Additional Information

- Use Master STAGES™ Whamex™ for a quick and thorough precleaning of your machine tool and coolant system.
- Consult Master Fluid Solutions before using on any metals or applications not specifically recommended.
- This product should not be mixed with other metalworking fluids or metalworking fluid additives, except as recommended by Master Fluid Solutions, as this may reduce overall performance, result in adverse health effects, or damage the machine tool and parts. If contamination occurs, please contact Master Fluid Solutions for recommended action.
- TRIM® is a registered trademark of Master Chemical Corporation d/b/a Master Fluid Solutions.
- Master STAGES™ and Whamex™ are trademarks of Master Chemical Corporation d/b/a Master Fluid Solutions.
- The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:

https://2trim.us/di/?i=eu_en_E950



Hasselsstraße 6-14

Düsseldorf, 40597

Germany

+49 211 41 72 82 00

info-eu@masterfluids.com

masterfluids.com/eu/en/

