


# TRIM™ TAP NC

## Nonchlorinated Tapping Fluid



TRIM TAP NC is a blend of synthetic and vegetable-based lubricants and additives with strong friction-reducing properties. Use for metals with low machinability at full strength for flooding applications involving broaching, sawing, milling, tapping, threading, gear cutting, shaving, gundrilling and reaming.

### Tapping



#### Added machinability:

*With strong friction-reducing properties, TRIM® TAP synthetic and synthetic blend straight oils are made for metals of low machinability. For added lubricity on extremely tough jobs, TAP oils ensure longer tool life, excellent surface finish, and parts size control.*

*All TAP products are compatible with all TRIM coolants.*

*Don't get tapped out — put TRIM TAP fluids to work for you.*

### Aerospace Approvals

Company	Specification
Applied Materials	UHV
Raytheon Technologies/Collins Aerospace/Pratt & Whitney	TO 10016

#### Choose TAP NC:

- Especially for taps up to 25mm diameter
- Promotes excellent finish
- Ensures parts size control
- Delivers exceptionally long tool life
- Reduces rubbing of the tool flank
- Compatible with most TRIM fluids
- Use for added lubricity on extremely tough jobs

#### TAP NC especially for:

**Applications** — broaching, gear cutting, gear shaving, gun drilling, milling, reaming, sawing, tapping and thread milling

**Metals** — aerospace aluminium alloys, cast aluminium, cast iron, chrome, exotic alloys, high tensile-strength steel, Inconel®, nickel alloys, stainless steels, steels, titanium, tool steels, yellow metals and zinc

**Industries** — aerospace and automotive

**TAP NC is free of** — chlorine, mineral oils, sulphur and zinc

#### Health and Safety

Request SDS



# TRIM™ TAP NC

## Nonchlorinated Tapping Fluid



### Application Guidelines

- TRIM TAP NC is designed to be used neat.
- For additional product application information, including performance optimisation, please contact your Master Fluid Solutions' Authorised Distributor at <https://www.masterfluids.com/eu/en/distributors/index.php>, your District Sales Manager, or call our Tech Line at +49 211 41 72 8 -900.

### Physical Properties Typical Data

Colour	Light brown
Odour	Fatty
Form	Liquid
Flash Point	> 149°C
Viscosity	66.00 mm <sup>2</sup> /s @40°C

### Ordering Information

20-litre pail

204-litre drum

TRIM™ TAP NC | ©2004-2026 Master Fluid Solutions™ | 2026-03-06

### Additional Information

- Use Master STAGES™ Whamex™ for a quick and thorough precleaning of your machine tool and coolant system.
- Consult Master Fluid Solutions before using on any metals or applications not specifically recommended.
- This product should not be mixed with other metalworking fluids or metalworking fluid additives, except as recommended by Master Fluid Solutions, as this may reduce overall performance, result in adverse health effects, or damage the machine tool and parts. If contamination occurs, please contact Master Fluid Solutions for recommended action.
- TRIM® is a registered trademark of Master Chemical Corporation d/b/a Master Fluid Solutions.
- Master STAGES™ and Whamex™ are trademarks of Master Chemical Corporation d/b/a Master Fluid Solutions.
- The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:

[https://2trim.us/di/?i=eu\\_en\\_TAPNC](https://2trim.us/di/?i=eu_en_TAPNC)



Hasselsstraße 6-14  
Düsseldorf, 40597  
Germany  
+49 211 41 72 82 00

[info-eu@masterfluids.com](mailto:info-eu@masterfluids.com)

[masterfluids.com/eu/en/](https://www.masterfluids.com/eu/en/)