

TRIM[®] TC 177

Odor Mask

TRIM TC 177 is a "vanilla" odor mask. This product may be used to reduce some of the odors associated with coolant systems.

Additives



The troubleshooters:

As cutting and grinding fluids can start to break down over time, tank-side additives can solve a number of problems. There are TRIM tank-side additives compatible with most coolants to extend tap and tool life, improve mechanical lubricity, control built-up edge, prevent stained parts, control foam, stabilize the emulsion, and replenish dye.

Whatever your problems and concerns, ask your TRIM specialist if a tank-side additive could be the answer.

Aerospace Approvals

Company	Specification
Raytheon Technologies/Collins Aerospace/Pratt & Whitney	PMC 9133



Choose TC 177:

- "Vanilla" odor mask

TC 177 especially for:

Applications — odor mask

Health and Safety

Request SDS



TRIM[®] TC 177

Odor Mask



Application Guidelines

- Very small amounts may be added directly to the working solution to reduce odor.
- Typical application rates are less than 6 ounces per 10,000 gallons.
- For additional product application information, including performance optimization, please contact your Master Fluid Solutions' Authorized Distributor at <https://www.masterfluids.com/na/en-us/distributors/index.php>, your District Sales Manager, or call our Tech Line at 1-800-537-3365.

Physical Properties Typical Data

Color (Concentrate)	Colorless to yellow
Odor (Concentrate)	Vanilla
Form (Concentrate)	Liquid
Flash Point (Concentrate) (ASTM D93-08)	> 199°F



2-quart tip "N" measure[®]
SKU: TC177-2Q
UPC-12: 641238010210



1-gallon jug
SKU: TC177-1G
UPC-12: 641238074267



5-gallon pail
SKU: TC177-5G
UPC-12: 641238010234



54-gallon drum
SKU: TC177-54G
UPC-12: 641238010241

Additional Information

- Use Master STAGES[™] Whamex[™] for a quick and thorough precleaning of your machine tool and coolant system.
- Consult Master Fluid Solutions before using on any metals or applications not specifically recommended.
- This product should not be mixed with other metalworking fluids or metalworking fluid additives, except as recommended by Master Fluid Solutions, as this may reduce overall performance, result in adverse health effects, or damage the machine tool and parts. If contamination occurs, please contact Master Fluid Solutions for recommended action.
- TRIM[®] is a registered trademark of Master Chemical Corporation d/b/a Master Fluid Solutions.
- Master STAGES[™] and Whamex[™] are trademarks of Master Chemical Corporation d/b/a Master Fluid Solutions.
- The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:

https://2trim.us/di/?i=na_en-us_TC177



501 West Boundary Street
Perrysburg, OH 43551-1200
United States
+1 419-874-7902

info@masterfluids.com

[masterfluids.com/na/en-us/](https://www.masterfluids.com/na/en-us/)