


WEDOLiT FS 3910

Straight Cutting and Bending Oil



WEDOLiT FS 3910 is non-water-soluble cooling lubricant with low viscosity for punching- and bending operations on steel and zinc coated steel. The product is not applicable for the treatment of nonferrous metals.



Physical Properties Typical Data

:		
:	0.00	
:	0.0	
:	0 °C	
:		

Application Guidelines

Storage must be frost-free between 10 - 40°C.
The minimum durability is 24 months in an original sealed package.

Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:
https://2trim.us/diw/?plr=FS-3910*en-th*th

WEDOLiT FS 3910
©0000-2024 Master Fluid Solutions™ | 2024-04-27

Choose WEDOLiT FS 3910:

- Can be applied undiluted by spraying, flooding, brushing or rolling
- Has a good spread effect, which causes an optimal even wettability of metal surfaces
- Has a simultaneously cleaning effect
- Contains a combination of aromatic free solvents with additives of esters and extreme-pressure compounds and is therefore practically odorless
- Is marked by a very fast evaporation with high flash point

Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

333/8 Moo 9, Bangpla, Bangplee
Samutprakarn, 10540
Thailand
+662 136 6319

thailand-info@masterfluids.com
masterfluids.com/th/en-th/

