


# Master STAGES™ CLEAN 2017

## Economical Heavy-duty Spray Cleaner



Master STAGES™ CLEAN 2017 is an economical heavy-duty spray cleaner that removes heavy soils and oily residues from ferrous and magnesium parts. Often used in rebuild operations and for cleaning up cast iron, stamped or drawn steel parts, or removing heavy RP coatings.

### Immersion



*Immersion washers effectively remove residue from light to heavy soils, light rust, coolant, oil, drawing compounds, lubricants, waxy soil, and corrosion inhibitors. Designed for cleaning aluminum, steels, cast iron, stainless steels, alloys, brass, bronze, copper, and magnesium and for multiple-metal situations, Master STAGES highly-concentrated cleaners allow immersion washers to run at lower concentrations and lower temperatures with increased bath life, less foam, and added corrosion protection.*

*Environmentally friendly, and free of SARA 313 reportable ingredients, cost-effective Master STAGES immersion cleaners ensure exceptional parts cleaning while using less product and less energy — for a better bottom line.*

### Choose CLEAN 2017:

- Very economical way to remove heavy soils and light rust
- Low foaming at ambient temperatures, and even lower when used above 120°F (49°C)
- Can be recycled using XYBEX equipment
- Contains no solvents, borates, silicates, nitrites, or amines
- Long bath life
- Excellent compatibility with magnesium
- Will prevent flash rusting and provide one-to-two days of in-process corrosion inhibition if not rinsed

### CLEAN 2017 especially for:

**Applications** — corrosion inhibition and parts washing

**Soils** — coolant residues, greases, oils, sulfurized oils, and waxes

**Metals** — cast iron, copper, magnesium, stainless steels, steels, and titanium

**Industries** — automotive, bearing, firearms, general engineering, general fabrication, general industry, job shop, machine tool, medical, and tool

**CLEAN 2017 is free of** — amines, borates, nitrites, silicates, and solvents

# Master STAGES™ CLEAN 2017

## Economical Heavy-duty Spray Cleaner



### Application Guidelines

- CLEAN 2017 is normally used at concentrations from 1%-7%. We recommend 3% as a starting concentration to provide reserve surfactant.
- This product is suitable only for steel, stainless steel, cast iron, titanium, pure copper, and magnesium parts. Do not use on aluminum alloy, copper alloy, or zinc.
- Operating temperature should be between 70°F to 210°F (21°C to 99°C) for spray cleaning.
- CLEAN 2017 will work well in immersion washers as well as ultrasonic baths under 120°F (49°C).
- High pH cleaners such as CLEAN 2017 often produce "soaps" as part of their cleaning action. CLEAN B1 is effective at reducing foam resulting from the formation of these soaps and may be used in conjunction with CLEAN 2017.
- For additional product application information, including performance optimization, please contact your Master Fluid Solutions' Authorized Distributor at <https://www.masterfluids.com/th/en-th/distributors/index.php> or your District Sales Manager, or email us at [thailand-info@masterfluids.com](mailto:thailand-info@masterfluids.com).


### Physical Properties Typical Data

Color (Concentrate)	Light yellow
Color (Working Solution)	Light yellow
Odor (Concentrate)	Mild, detergent
Form (Concentrate)	Liquid
Flash Point (Concentrate) (ASTM D92-90)	> 100°C
pH (Concentrate as Range)	13.5 - 14.0
pH (Typical Operating as Range)	12.5 - 13.0
V.O.C. Content (EPA Method 24)	0 lbs/gal
Cleaner Conductivity Factor	0.00020
Titration Factor (CL-1 Titration Kit)	0.36
Number of Cleaner Vials (CL-1 Titration Kit)	1.0
Cleaner Indicator A or B (CL-1 Titration Kit)	A

### Recommended Metalworking Concentrations


Design Concentration Range	1.0% - 7.0%
----------------------------	-------------

### Concentration by Conductivity



$$\% \text{ Concentration} = \text{Conductivity in Micro Siemens} \times \text{Factor}$$
$$\text{Conductivity Factor} = 0.00020$$

### Concentration by Titration



$$\% \text{ Concentration} = \text{No. of Drops} \times \text{Titration Factor}$$
$$\text{Titration Factor} = 0.36$$

### Health and Safety

Request SDS



# Master STAGES™ CLEAN 2017

## Economical Heavy-duty Spray Cleaner



### Mixing Instructions

- Recommended usage concentration in water: 1.0% - 7.0%.
- To help ensure the best possible working solution, add the required amount of concentrate to the required amount of water (never the reverse) and stir until uniformly mixed.

### Ordering Information

20-liter pail

204-liter drum

1000-litre IBC

Master STAGES™ CLEAN 2017 | ©2021-2025 Master Fluid Solutions™ | 2025-12-18

### Additional Information

- Industrial use only
- Consult Master Fluid Solutions before using on any metals or applications not specifically recommended.
- This product should not be mixed with other metalworking fluids or metalworking fluid additives, except as recommended by Master Fluid Solutions, as this may reduce overall performance, result in adverse health effects, or damage the machine tool and parts. If contamination occurs, please contact Master Fluid Solutions for recommended action.
- Master STAGES™ is a trademark of Master Chemical Corporation d/b/a Master Fluid Solutions.
- The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:  
[https://2trim.us/di/?i=th\\_en-th\\_CLEAN2017](https://2trim.us/di/?i=th_en-th_CLEAN2017)



333/8 Moo 9, Bangpla, Bangplee  
Samutprakarn, 10540  
Thailand  
+662 136 6319

[thailand-info@masterfluids.com](mailto:thailand-info@masterfluids.com)

[masterfluids.com/th/en-th/](https://masterfluids.com/th/en-th/)