

Master STAGES™ Whamex™

Machine Tool Sump and System Cleaner



Master STAGES™ Whamex™ is a safe, fast-acting concentrated formula that will save machine cleaning downtime while removing the oily residues, scums, and insoluble soap deposits that reduce coolant life.

Whamex is made for cleaning out machine tool sumps and larger systems, coolant supply lines, and coolant recycling equipment. Whamex is compatible with most waste treatment (including ultrafiltration) and will not degrade TRIM metalworking fluids when used as directed.

Maintenance



Whether cleaning true grit or light soil from machines, work surfaces, glass, or floors, there's a highly-concentrated, cost-effective Master STAGES cleaner to get the job done and save hours of maintenance. So, don't just get it clean — get it Master STAGES clean! Master STAGES highly concentrated Whamex™ sump and central system cleaners for interim and full cleanouts extend sump life, are very cost effective, and greatly reduce downtime.

All Master STAGES environmentally-friendly products are safe for human contact and free of harmful, corrosive chemicals and troublesome SARA 313 ingredients.

Choose Whamex:

- A very specialized formula that draws many years of hands-on experience in machine clean outs
- Quickly breaks down and lifts off insoluble scum deposits hidden in lines and difficult to reach areas — getting rid of these residues is one of the best ways to extend coolant life in your system
- Very hard water tolerant allowing it to be effective in raw water or used coolant
- Environmental approvals are simplified because Whamex contains no nitrites, phosphates, barium, phenols, or butyl cellulose; this formula has very low V.O.C. content and no SARA 313 reportable ingredients
- When used as directed below, this product is compatible with TRIM brand semisynthetic and soluble oil coolants, as well as most competitive coolants. Will remove heavy soils from machines without affecting paints, coatings, seals, hoses, or skirting, and it won't leave a slippery residue
- Short-term corrosion inhibitors prevent flash rusting of machine surfaces and ways

Whamex especially for:

Applications — machine cleaning inside and machine cleaning outside

Soils — coolant residues, heavy oils, and light oils

Metals — cast iron and steels

Industries — aerospace, automotive, machine tool, and medical

Whamex is free of — 2-butoxyethanol (Butyl), barium, nitrites, NPEs, phenols, phosphate, and SARA 313 listed ingredients

Master STAGES™ Whamex™

Machine Tool Sump and System Cleaner



Application Guidelines

- Machine cleaning for machines using emulsion cutting fluids
- Use a high-flow sump cleaner such as a Yellow Bellied Sump Sucker™, to quickly remove spent fluids and residues.
- Add up to 0,1% Master STAGES™ CLEAN DF1 to control foam in high-pressure, high-flow systems.
- All used coolant or rinse water must be recycled or disposed of in accordance with local, state, or provincial, and national environmental regulations.
- To learn about the "Preferred Method for Cleaning Machine Tools and Central Systems"; and the "Quick Cleaning Method For Noncritical Interim Cleaning" check out pages 10-12 of the [The Handy Pocket Guide to a Clean Shop](#).
- For additional product application information, including performance optimization, please contact your Master Fluid Solutions' Authorized Distributor at <https://www.masterfluids.com/vnm/en-vnm/distributors/index.php>, your District Sales Manager, or email us at vietnam-info@masterfluids.com.


Physical Properties Typical Data

Color (Concentrate)	Yellow
Color (Working Solution)	Colorless
Odor (Concentrate)	Mild pleasant
Form (Concentrate)	Liquid
Flash Point (Concentrate) (ASTM D92-90)	> 100°C
pH (Concentrate as Range)	10,5 - 11,5
pH (Typical Operating as Range)	10,0 - 11,0
Coolant Refractometer Factor	2,5
Cleaner Conductivity Factor	0,00186
Titration Factor (CL-1 Titration Kit)	0,43
Number of Cleaner Vials (CL-1 Titration Kit)	2.0
Cleaner Indicator A or B (CL-1 Titration Kit)	B

Recommended Metalworking Concentrations


Design Concentration Range 1,0% - 15,0%

Concentration by Conductivity



% Concentration = Conductivity in Micro Siemens x Factor
Conductivity Factor = 0,00186

Concentration by Titration



% Concentration = No. of Drops x Titration Factor
Titration Factor = 0,43

Health and Safety

Request SDS



Master STAGES™ Whamex™

Machine Tool Sump and System Cleaner



Mixing Instructions

- Recommended usage concentration in water: 1,0% - 15,0%.
- To help ensure the best possible working solution, add the required amount of concentrate to the required amount of water (never the reverse) and stir until uniformly mixed.

Ordering Information

20-liter pail

204-liter drum

1000-liter tote

Master STAGES™ Whamex™ | ©2022-2026 Master Fluid Solutions™ | 2026-05-05

Additional Information

- Industrial use only
- Consult Master Fluid Solutions before using on any metals or applications not specifically recommended.
- This product should not be mixed with other metalworking fluids or metalworking fluid additives, except as recommended by Master Fluid Solutions, as this may reduce overall performance, result in adverse health effects, or damage the machine tool and parts. If contamination occurs, please contact Master Fluid Solutions for recommended action.
- Master STAGES™ is a trademark of Master Chemical Corporation d/b/a Master Fluid Solutions.
- The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:

https://2trim.us/di/?i=vnm_en-vnm_WHAMEX



17th Floor, VCCI Tower, 9 Dao Duy Anh Street, Phuong Mai Ward, Dong Da District

Hanoi City, 115500

Vietnam

+84 24-3512-3436

vietnam-info@masterfluids.com

masterfluids.com/vnm/en-vnm/

